NAViQ

TECHNICAL SPECIFICATIONS

Product name:	MAGNETIC TRACK TAPE
Product description:	Adhesive Magnetic Rubber Tape for AGV Guidance
Product Reference:	MTRK ww p rr rr: Length per Roll (meters) p: Magnetic Polarity: N= North on Top side, Adhesive on South Side S= South on Top side, Adhesive on North Side ww: Tape Width (milimeters)
Composition:	·
PLASTOFERRITE CM2	Generic description: PLASTOFERRITEGrade: CM2Aspect: SolidColor: Dark BrownDensity: $3.5 \div 3.8 \text{ g/cm}^3$ Working temperatura range: $20^{\circ}C \div 80^{\circ}C$ Magnetic Properties under normal conditions :Br: $0,24 \div 0,25 T$ Hcb: $150 \div 166 \text{ kA/m}$ Hcj: $\geq 150 \text{ kA/m}$ (B.H)max: $10 \div 12 \text{ kJ/m}^3$
3M Adhesive Double Coated Tissue Tape 55236	General Description: Acrylic double sided adhesive Front face: Acrylate, 0.06 mm Back side: Acrylate, 0.06 mm Adhesive protective paper: white with 3M logo
Magnetic Polarity	Polarity N Polarity S North South Adhesive South North Adhesive Note: For polarity determination, the North side of the tape will turn to face the earth's North pole when unconstrained. Warning: Do not bring in proximity to magnets. Tape polarity and flux can be affected and values can change substantially.
Physical Dimensions	350mm +/-10mm
Storage	Store magnetic tape in dry environments and away from heat sources
Orderable References	MTRK50N5050 mm wide magnetic tape with North top side. 50m (150ft) rollMTRK25N5025 mm wide magnetic tape with North top side. 50m (150ft) rollMTRK50S5050 mm wide magnetic tape with South top side. 50m (150ft) rollMTRK25S5025 mm wide magnetic tape with South top side. 50m (150ft) rollMTRK25S5025 mm wide magnetic tape with South top side. 50m (150ft) rollNote:Naviq recommends North top side polarity for main track in new installations